

## welloStationX – The only automated, FDA-cleared, no-touch clinical thermometer.

Whether you're responsible for an office building, a school, a place of worship, or any other communal setting, you need a solution in place to help actively safeguard your environment.

Rest easy knowing you've done your part to keep facilities safe for employees and visitors. Wello's rapid, non-intrusive facial scan catches even subtle temperature elevations that could indicate infection.



## welloStationX SYSTEM SPECIFICATIONS

Mechanical/Environmental	
Dimensions	19.50" W x 57.50" H x 14.50" D
Weight	37.5 lbs
Operating Temperature	15°C to 28°C (59°F to 82.4°F)
Storage Temperature	-20°C to 50°C (-4°F to 122°F)
Measurement Range	35°C to 42°C (95°F to 107.6°F) Adjusted Mode of Operation
Power Supply*	<b>Power Input:</b> 100-240VAC <b>Power Output:</b> 5V, 3A DC
Relative Humidity	20-70% humidity, non-condensing
System Architecture	
Processor	Broadcom BCM2836
Operating System	GNU/Linux
Memory	16 GB
Display	10.1" HDMI Backlit LCD
Thermometer	21 x 21-pixel matrix with 2° increments, 16" focal plane
Sensor Accuracy	±0.2°C (±0.36°F) (based on manufacturer specifications)
Camera	5 MegaPixel
Transient Response Time	30 ms
Start-Up Time	30 sec
Wireless Connectivity	Yes (Ethernet Connection Recommended)
Throughput	350 scans/hour
Warranty	1-year warranty (extended options available upon request)